

UNICON

Containerbau +
Vermietung GmbH



6' 8' DNV 2.7-1/EN12079 offshore container with removable shelf

Advantages

Equipped with checker plate steel floor / offshore pad-eyes within ISO / low tare – high payload

TIR / DNV 2.7-1 EN12079 / NORSOK M501-A1

Optional supplied with DNV 2.7-1 certified wire rope superlooped sling (rigging)

Upper and lower lashing points on three sides.

- From stock available for sales and rental
- Modification work possible under Lloyds certification
- Some of our other designs are: 10' half height / 10' 8'6" dnv / 20' half height heavy duty / 20' 8'6" dnv / 20' 8'6" low roof / 20' 8'6" open top / 20' 9'6" high cube

Classification		Dimension			
External	Length	1.830	+0 -3mm	6' 0"	+0 -1/8"
	Width	1.830	+0 -3mm	6' 0"	+0 -1/8"
	Height	2.438	+0 -3mm	8' 0"	+0 -3/16"
Internal	Length	1.675	mm	5' 5 ¹⁵ / ₁₆ "	
	Width	1.734	mm	5' 8 ¹⁷ / ₆₄ "	
	Height	2.170	mm	7' 1 ⁷ / ₁₆ "	
Door opening	Width	1.726	mm	7' 8 ³ / ₆₄ "	
	Height	2.074	mm	7' 4 ⁵ / ₈ "	
Internal cubic capacity		6,3	CU.m	222.6 CU.ft	
Max. gross weight		6.620	kg	14.594 lb	
Tare weight		1.620	kg	3.571 lb	
Maximum payload		5.000	kg	11.020 lb	